



## SIP IP PA AP-S9A15 15W PoE Power Mini Wall Amplifier



## AP-S9A15 15W PoE SIP IP Mini Wall Amplifier

### Features :

- SIP Desktop Calling Paging station for control and make announcement or intercom into all SIP PA system
- Can be announcement to individual speakers or group SIP speaker
- Built-in high speed industrial chip, start time less than 1 second
- Compatible with AVAYA, ALCATEL, CISCO, HUAWEI and many more SIP server softwares
- Online and Offline paging mode which ensure 24/7 paging facility
- Two way communication between field device to paging device
- Supports Line in and output, G.711 audio, Pre stored voice announcements
- Hands-free call and program broadcast receiving
- Built-in 7" LCD display easy to use
- Wide range protocol SIP/IP/ARP/IGMP/ICMP/DNS/DHCP/UDP
- Built-in microphone, 3W monitor speaker with clear voice and no echo noise
- External audio input, Audio output for external active speaker
- Dual power selectable 24V or 12V DC (before ordering, default 12V)
- Elegant and modern design with exquisite appearance

### APPLICATIONS

#### Government & Corporates



#### Industries & Plants



#### Stations & Airports



## Technical Specifications

Model No.	AP-S9A15
Power out	2 x 15W
Audio output	1 Audio out, 1 Speaker out
Volume control	Yes
Network protocol	SIP,TCP,UDP,DNS,ARP,IGMP,ICMP
Network speed	RJ-45(10/100Mbps)
Audio compression	ADPCM,MP3, MP2, PCM, WMA,WAV
Audio bitrate	8kHz-44.1kHz
Audio delay	<100 ms
S/N ratio	≥90dB
Frequency	20Hz-22KHz
Power Input	DC-12V, DC-24V or POE
Mount	Wall mount or Table top
Working temp. & Humidity	-10°C ~ 50°C, ≤ 90%RH (Not condensing)
Enclosure & Color	Full Metal, Black
Dimension & Weight	30(H) x 100(W) x 70(D) mm, <0.7Kg

