



SIP IP PA AP-SW15P SIP 15W PoE Wall Mount Speaker



AP-SW15P SIP 15W PoE Wall Mount Speaker

Features :

- PoE powered IP network 15W wall mount speaker
- Compatible with both IEEE 802.3af & IEEE 802.3at
- 5" full range ceiling speaker, Built-in class-D amplifier
- High speed ARM+DSP Processor
- Speaker can be set in several Groups or Zones
- Paging priority, Remote volume control
- Broadcast of various music or pre-recorded voice messages possible
- Supports multiple audio types MP3/WMA/WAW(optional G.711U/G.711A)
- Emergency input and output for third party system integration(optional)
- Redundant design PoE & DC12V power supply
- Ideal for background music, paging system and voice alarm system

APPLICATIONS


Government & Corporates



Industries & Plants



Stations & Airports



Technical Specifications

Model No.	AP-SW15P
Rated power	15Watts RMS
Built-in amplifier	15W RMS & Max. 20W
Network protocol	SIP, DNS, DHCP, TCP
Speaker type	Two-Way 5" woofer + 1.5" tweeter
Power	DC-12V, POE 802.3af or POE 802.3at
SPL	92dB at 1W/1M
Network port	RJ-45(10/100Mbps)
Audio type	MP3, MP2
Audio bitrate	8K-512Kbps
Frequency response	100Hz-18KHz(\pm 3dB)
THD	\leq 1%
S/N ratio	\geq 85dB
Dimension	295(H) x 195(W) x 155(D)mm
Working temp.	-30°C ~ 55°C
Installation	Wall mount, U-shaped bracket(aluminium)
Enclosure	ABS plastic(UV-protected), Metal grille(black or white)
Weight	<4Kg

