


AP-Z214 16 Zone Keypad]Paging Station

Features:

- Flexible with long distance audio transmission
- Paging up to 16pcs of AP-Z215 at 160 zones
- High sensitivity gooseneck Microphone and line In
- Built in Pleasant chime control
- 4 priority levels, First Priority to MIC1 for EMC, Remote paging MIC and Last as Aux
- 1 MIC, 2 Aux and 4 Remote Paging Microphone Input
- Long distance communication between Paging station to Controller up to 1KM
- LED Indicator display for Status, Paging Zones, etc.
- All Zone, Individual Zone call function, Automatic Mute Function
- Max. 4 no's AP-Z214 Units supports In One System

APPLICATIONS







info@avtrontech.com avtrontech.com



Technical Specifications

Model No.	AP-Z214
MIC Input Gooseneck	MIC: 600 Ohm 5mV, unbalanced, XLR
Line Input	10K Ohm, 775mV, unbalanced, RCA Jack
Line Output	>775mV at OdB, unbalanced
Control Zone	Channel 1 to 10
Frequency Response	MIC:100Hz - 15KHz, Line: 20Hz - 15KHz at +/-3dB
S/N Ratio	>70dB
THD	Less than 0.01% at 1KHz
Mute Attenuation	Line1 and MIC mute Line 2 at 0 ~ 30dB
Power Input	200-240V AC
Power Consumption	<8W
Mount	Table Top
Enclosure & Color	Full Metal, Black
Dimension & Weight	80(H) x 75(W) x 205(D) mm, <2.5Kg

