



PA Speaker AP-IP600TM IP PA Touch Based Paging Station



AP-IP600TM IP PA Touch Based Paging Station

Features :

- Touch screen IP remote microphone or IP call station for IP public address system
- Full duplex two way communication between different remote microphones
- With 7 inch LCD to control up to 6,000 speaker zones
- With programmable swift key for automatic control
- Several paging capacity: zone paging, group paging, all zone paging, two way intercom
- Built-in 3W full-range monitor speakers with clear voice restoration and no echo noise
- With USB input to broadcast pre-recorded voice message to different zones
- Enable to transmit local sources to be broadcasted over network
- Embed PC technology, built-in DSP & high speed industrial chip to ensure start time less than 1 second
- Within one microphone input and one line input and one line output for sound system
- 12V DC power supply, the power adapter is included in the packaging

APPLICATIONS

Commercial Building



School Campus



Transportation



Technical Specifications

Model No.	AP-IP600TM
Description	IP Network Remote Microphone (Touch Screen)
Communication Protocol	TCP/IP, UDP, IGMP, ARP, UDP
Audio Format	MP3/MP2
Sampling Rate	8K~48KHz
Transmission Speed	10M/100Mbps
Frequency Response	20Hz~16KHz (+1dB, -3dB)
T.H.D.	≤0.3%
S/N Ratio	>70dB
Connector	One RJ45 port, one line input, one line output, one mic input, one USB input
Working temp	-5 °C~ +40°C
Humidity	10% ~ 90%
Power Consumption	≤10W
Power Supply	DC 12V
Dimensions	250x163x42mm
Weight	2.2Kg

