



Network PA AP-ECS30 30W Outdoor IP Column Speaker



AP-ECS30 30W Outdoor IP Column Speaker

Features :

- IP PA active 30W Column Mount Loud Speaker
- 5" full range Two-Way Ceiling Speaker, Built-in class-D Stereo Amplifier
- Wide range of Network protocol TCP, UDP, IGMP
- Multiple options of audio codec like MP3, MP2
- IP Speakers support over existing LAN/WAN/Internet System
- Emergency input and output for third party system integration like CCTV, fire, access control (optional)
- Paging priority, Remote Volume Control
- Simultaneous broadcast of various music or pre-recorded messages
- Scheduled broadcasting for ring bell or pre stored audio messages
- Dust free and waterproof IP65 rated design for in/outdoor use
- Column Mount Speaker with mounting bracket
- Ideally for parks garden, playground, parking and many more

APPLICATIONS

Commercial Building



School Campus



Transportation



Technical Specifications

Model No.	AP-ECS30
Rated power	RMS 30W
Speaker type	Two-Way 5" woofer + 1.5" tweeter
Power	AC220V ± 10% 50-60Hz
SPL	92dB at 1W/1M
Network port	RJ-45(10/100Mbps)
Network protocol	TCP,UDP,IGMP
Audio type	MP3, MP2
Audio bitrate	8K-512Kbps
Frequency response	80Hz - 16KHz(±3dB)
THD	≤1%
S/N ratio	≥70dB
Dimension	190(D) x 175(W) x 320(H) mm
Working temp.	-30°C~ 55°C
Installation	Column/Wall mount outdoor
Enclosure	Aluminum, White/Black finish
Weight	<2.8Kg

