



Network PA AP-N9E30W IP PA 30W Wall Amplifier



AP-N9E30W IP PA 30W Wall Amplifier

Features :

- 2ch 30W IP PA mini wall Amplifier
- High Speed ARM+DSP Processor
- Support directly connection of Speaker/Amplifier
- Supports LAN/WAN ethernet system, Gateway and Router
- 1 Analog MIC input with local volume control
- 1 Analog Audio Output to connect External Amplifier
- Line, MIC input with local volume control
- Audio Input, Line Output, 24V, Relay out
- Network protocol supports TCP,UDP,IGMP, etc.
- Multiple audio codec like MP3, WAV, etc.
- Power up time is <1sec
- Compact and wall mount installation design

APPLICATIONS

Commercial Building



School Campus



Transportation



Technical Specifications

| Model No. | AP-N9E30W |
|--------------------------|---------------------------------------|
| Power out | 2 x 30W |
| Audio input | 1 MIC in, 1 Aux in , 1 Audio in |
| Audio output | 1 Line out, 1 DC 24V out, 1 Relay out |
| Control | Volume control Line & MIC in |
| Network protocol | TCP,UDP,IGMP,ICMP,ARP, DNS |
| Network Port | RJ-45(10/100Mbps) |
| Audio compression | ADPCM,MP3, MP2, PCM, WMA,WAV |
| Audio bitrate | 8kHz-44.1kHz, 16bit, 8kbps ~ 320kbps |
| Audio delay | <30 ms |
| S/N ratio | ≥90dB, 20Hz-22KHz |
| Power | 24V DC |
| Mount | Table top, Wall Mount |
| Working temp. & Humidity | -0°C ~ 50°C, ≤ 90%RH (Not Condensing) |
| Enclosure & Color | Full Metal, Black |
| Dimension & Weight | 35(H) x 150(W) x 132(D) mm, <0.7Kg |

