



Network PA AP-N9EPM20 IP Keypad Remote PA Paging Station



AP-N9EPM20 IP Keypad Remote PA Paging Station

Features :

- Network Desktop Paging Station for remote paging in all network PA products
- All zone, Group zone, Individual zone, selected zones and two way by paging keypad
- Built-in embedded OS, DSP and high speed industrial chip to ensure start time less than 1 second
- Online and Offline paging mode which ensures 24/7 paging facility
- Two way communication between field device and paging device
- Single button push to answer the intercom devices
- Chime warning and flashing indicators
- Hands-free call and program broadcast receiving
- Built-in 3.4" LCD display, Numeric keys, functions keys, easy to use
- Built-in Microphone, 2W monitor speaker with clear voice and no echo noise
- External Microphone Input, Aux Input and Output
- Dual power selectable 24V or 12V DC (before ordering, default 12V)
- Elegant and modern design with exquisite appearance

APPLICATIONS

Commercial Building



School Campus



Transportation



Technical Specifications

Model No.	AP-N9EPM20
MIC	Gooseneck Type (detachable)
External MIC	Yes
Audio Input	1 Aux in
Audio Output	1 Aux out
Monitor Speaker	Yes, 2W
Display Screen	TFT 2.8" LCD
Network protocol	TCP,UDP,IGMP,DNS, ARP
Network port	RJ-45(10/100Mbps)
Audio compression	MP3, MP2
Audio bitrate	8kHz~48kHz
S/N ratio	≥ 70dB
Frequency response	20Hz-16KHz(+1dB, -3dB)
Power	DC Power
Power consumption	< 10 W
Working temp. & Humidity	-0 °C ~ 50 °C, ≤ 90%RH (Not Condensing)
Mount	Table Top
Enclosure & Color	Full Metal, Black
Dimension & Weight	50(H) x 210(W) x 150(D) mm, <2.5Kg

