



## Network PA AP-N9RPM Network PA Paging Station



# AP-N9RPM Network PA Paging Station

### Features :

- Network Paging Station remote paging solution for Network PA system
- All Zone, Group Zone, Individual zone and selected zones paging options
- Max support 300 call stations working at simultaneous
- Built-in LCD display, Power and Zone selection
- Built-in microphone, monitor speaker for two way intercom use
- Eight zone selector, microphone on and number buttons
- Nine levels of priority setting in the software
- Power up time is <2sec
- Aux input and output for external devices

### APPLICATIONS

Commercial Building



School Campus



Transportation



## Technical Specifications

Model No.	AP-N9RPM
MIC	Gooseneck type
Audio Input	1x Aux In
Audio Output	1x Aux Out
Display Screen	TFT 1.8" colorful LCD, 128×160 resolution
Network Protocol	TCP,UDP,IGMP,ICMP,ARP
Network Port	RJ-45(10/100Mbps)
Audio Compression	ADPCM,MP3, MP2, PCM
Audio Bitrates & Sampling	8kHz~44.1kHz, 16bit
S/N Ratio	≥90dB
Audio Delay	<30ms
Frequency Response	20Hz-20KHz
Power Input	DC 9V
Power Consumption	<5W
Working Temp. & Humidity	-10 °C ~ 50 °C, ≤ 90%RH (Not condensing)
Mount	Table Top
Enclosure & Color	Full Metal, Black
Dimension & Weight	66(H) x 245(W) x 122(D) mm, <1.4Kg

