



Network PA AP-N9WAR 20W Network Wall Amplifier



AP-N9WAR 20W Network Wall Amplifier

Features :

- 20W Network wall Class D Amplifier
- Built-in Audio Controller with 20W class-D amplification with power out 8 Ohms
- Installed Microphone on the terminal to enable the monitor on-site activities from main control room
- Supports LAN/WAN ethernet system, Gateway and Router
- Priority announcement programming network program, local mic input and local line input
- 1 Analog Audio output to connect external Amplifier
- Wide range of Network Protocol such as TCP,UDP,IGMP,ICMP,ARP
- Multiple options of audio codec like ADPCM,MP3, MP2, PCM
- Built In colorful 3 Line LCD display, Infrared Remote Controller
- Power up time is <1sec
- Less emission of the heat and higher efficiency
- Wall mount installation design

APPLICATIONS

Commercial Building



School Campus



Transportation



Technical Specifications

Model No.	AP-N9WAR
Power Output	2x10W (8 Ohms)
Audio Input	1x MIC Input, 1x Aux Input
Audio Output	1x Line out, 1x Speaker Out Low Impedance
Network Protocol	TCP,UDP,IGMP,ICMP,ARP
Network Port	RJ-45(10/100Mbps)
Audio Compression	ADPCM,MP3, MP2, PCM
Audio Bitrate & Sampling	8kHz-44.1kHz, 16bit, 8kbps ~ 320kbps
Audio Delay	<100 ms
S/N Ratio	≥90dB, 20Hz-22KHz
Alarm	1 x Dry Contact In, 1x Dry Contact Out
Power Input & Consumption	DC 12V, <25W
Mount	Table top, Wall Mount
Working Temp. & Humidity	-10°C ~ 50°C, ≤ 90%RH (Not condensing)
Enclosure & Color	Full Metal, Silver
Dimension & Weight	250(H) x 186(W) x 50(D) mm, <0.7Kg

