



PA Amplifier AP-PCD150 Class-D Single Channel 500W Power Amplifier



AP-PCD150 Class-D Single Channel 500W Power Amplifier

The PCD range digital class-D power amplifier is of switching power technology, which features of minimum power consumption and much higher efficiency up to 85%, moreover it helps to save installation rack space, generate less heat so as to extend its performance life span as a result.

The PCD150 is of rated power output at 500W, so it could be used as digital public address system at minimum cost.

The versatile loudspeaker outputs of both high impedance 100V & low impedance 4-16ohms enable it meet both PA fixed installation and Hi-fi stereo sound installation jobs.

There are one balanced inputs by phoenix connector with gain control. Speaker outputs both by 100V & 4-16ohms. The built-in high-pass filters could be enabled or disabled through the dip switch pre-setting.

Automatic standby enable after no detection of signal input for one minute, immediately wake up at sight of any input. Visual working status indicators include protection, clip, input and output for easy supervision. With complete short circuit, overload, high temp, clip and DC protection.

Switchable AC power supply from 115V to 230V, thus it support worldwide sound system installation. DC24V operation is optional at order request for immediately shipment as well.

Features :

- Switching power technology digital power amplifier
- Class-D PA power amplifier of minimum power consumption
- Less rack space and less heat generation
- Single channel power amplifier into 19" rack mount unit
- Rated power output at 120W
- Speaker outputs 4-16Ω/100V
- Balanced XLR input by phoenix connector
- Each input with separate gain control.
- Each channel with high-cut filter.
- Built-in auto standby feature to save power consumption
- Separate indicators for protection, clip, input and output
- Complete short circuit, overload, high temp, clip and DC protection
- Wide AC input switchable between 115V and 230V
- 24V DC input as option at order request.

Technical Specifications

Model No.	AP-PCD150
Amplifier	Class-D Power Single Channel
Rated Power Output	500W
Speaker Out	100V, 4 ~ 16Ω
Frequency response	L/H Cut OFF 20Hz-20KHz (+ 1/-2dB) L/H Cut ON 70Hz-10KHz (+ 1/-3dB)
S/N Ratio	>80dB
Crosstalk	>60dB, 1KHz, Max output
Input Impedance	10Kfi
Input	0.775V, 0dBu, balanced phoenix connector
THD	<0.1% (1KHz/-3dB, 100W)
Protection	short circuit, overload, high temp, clip and DC protection.
Power Input	220V AC Input, 50 ~ 60Hz (115V & 24V-DC Input Optional)
Power Consumption	700W
Working Temp. & Humidity	-5°C ~ 40°C, ≤ 95%RH (Not condensing)
Mount	19" Rack Mount, Table Top
Enclosure & Color	Full Metal, Black
Dimension	44(H) x 485(W) x 420(D) mm

APPLICATIONS

Auditorium & Outdoor Events



Disco Clubs & Restaurant



Apartment & Corporates

