

AP-Z215 10 Channel Paging Selector

Features:

- 10 Zone Paging Selector and expandable up to 160 Zone
- up to 10 Contact In and Output
- Built in Pleasant Chime Control
- 4 priority levels, Highest MIC1 priority to EMC MIC, Remote paging MIC and aux as last
- 1 MIC, 2 Aux and 4 Remote Paging Microphone Input
- Directly Input from OD-Z221 to EMC1 can generate emergency Annoucment & Alarm Siren for connected devices
- LED Indicator display for all the zones
- 19" Ready rack mount Installation design

APPLICATIONS







info@avtrontech.com avtrontech.com



Technical Specifications

Model No.	AP-Z215
MIC Input	600 Ohm 5mV, unbalanced
Line Input	10K Ohm, >220mV, unbalanced
Line Output	>775mV at 0dB, unbalanced
Frequency Response	MIC:100Hz - 15KHz, Line: 60Hz - 15KHz at +/-3dB
S/N Ratio	>70dB
THD	Less than 0.01% at 1KHz
Mute Attenuation	Line1 and MIC mute Line 2 at 0 ~ 30dB
Power Input	200-240V AC, Fuse Protection
Power Consumption	<15W
Mount	2U 19" Rack Mount, Table Top
Enclosure & Color	Full Metal, Black
Dimension & Weight	89(H) x 483(W) x 366(D) mm, <7Kg

