



PA Amplifier AP-ZPS 6 Zone Remote Paging Station



AP-ZPS 6 Zone Remote Paging Station

Features :

- Built-In 6 Zone Remote Paging Microphone
- Max. supported 6 remote microphones with one amplifier
- Multiple remote microphones cascaded together for use.
- Chime pre alert before announcement
- 6 Zone selection, Three color Indicators(Power, Message, Busy)
- Reset/Cancel, All zone call, Individual call buttons
- Master & slave configuration with two RJ45 Ports Input/Expansion out
- microphone volume control and aux input.
- Cat-5/6 communication and max up to 300M
- Dual Power Options Powered by Amplifier/DC24V

APPLICATIONS



Technical Specifications

Model No.	AP-ZPS
MIC	Gooseneck type
Zone selection	6 Zones
System capacity	6 Paging Station in one amplifier
MIC input	5mV, 600Ω
Aux input	350mV, 10kΩ
S/N ratio	≥70dB
THD	<1%, 1KHz
Frequency response	80Hz ~ 16KHz
Power input	Powered by Amplifier, DC 24V
Power consumption	<3W
Working temp. & Humidity	-20°C ~ 70°C, ≤ 95%RH (Not condensing)
Mount	Table Top
Enclosure & Color	Full Metal, Black
Dimension & Weight	50(H) x 175(W) x 155(D) mm, <1.2Kg

