



IP Camera AM-DM4064-FMA2 H.265+ 4MP Super WDR 50M ExIR IP Bullet Camera



Superior Engineering Design & Sensational Image Quality

AM-DM4064-FMA2 H.265+ 4MP Super WDR 50M ExIR IP Bullet Camera



SUPER WDR



H.265 + VIDEO COMPRESSION



VIDEO ANALYTICS



REGION OF INTEREST



SMART IR



MECH. IR CUT FILTER



MOTION DETECTION



LOCAL STORAGE 512GB



AUDIO IN/MIC




VOLTAGE PROTECTION 6KV/2KV ELECTRIC PROTECTION

Features :

- 1/2.8" Progressive scan CMOS image sensor
- Powerful H.265+ Hardware compression along With H.264, MJPEG
- 25fps at 4MP resolution 2560(h) x 1440(v) pixel, 3MP, 2MP, 1.3MP
- Built-in Mic, SD Card Slot, Reset Button
- Super 120dB WDR(Wide dynamic range) & 3D DNR(Digital noise reduction)
- Wide viewing angle 4.0MM high definition fixed focus lens
- High intensity ExIR LED up to 50Mtrs. night vision, TDN by dual filter(ICR)
- Low illumination at Color: 0.002Lux@ (F1.6, ACG ON), B/W: 0Lux with IR
- Smart IR function works when object/person is close to camera. It controls IR to get clear picture
- Software compatibility with icrys series 256Ch CMS software and any third party Onvif VMS/CMS Software
- P2P secure cloud monitoring on iOS/Android handsets(through NVR live/playback/audio and control)
- Built in uni/multicast streaming to support multiple users logging at same time
- Wide range network protocol TCP/UDP/FTP/RTSP/HTTP & many more
- Various modes for light compensation such BLC/HLC, AGC, Shutter speed
- Image enhancement by White balance, picture color, Day/Night mode & noise reduction
- OSD in multiple color, naming & position, Privacy, Motion detection
- ONVIF S profile, Email notification, Manual & Schedule snapshot, Manual recording
- Easy, fast response & friendly graphical user interface, Advanced encryption secure access
- Redundant power supported by 12VDC & PoE(power over ethernet) with 802.3af standard
- Built in TVS protection 4000V & lightning/surge Power(2000V), RJ45(1000V)
- Waterproof IP67 housing that supports wall/ceiling mounts included 3 Axis Bracket

Super WDR



Technical Specifications

| Model No | AM-DM4064-FMA2 |
|------------------------------------|---|
| Camera Specification | |
| Sensor type | 1/2.8" progressive scan CMOS sensor |
| Lux Level(illumination) | Color: 0.002Lux@ (F1.6, ACG ON), B/W: 0Lux with IR |
| Shutter speed | Auto/Manual, 1s ~ 1/100,000s |
| AGC | Yes |
| Lens | 4.0MM fixed focus |
| IR distance | IR up to 50 Meter |
| IR function | Smart IR, ICR Dual Filter, IR LED power adjustable |
| Compression/Video/Audio | |
| Video Compression | H.265+, H.265, H.264+, H.264, MJPEG |
| H.264/H.264+ Profile | Main, High, Baseline |
| Main stream | 4MP(2560x1440P)/3MP(2304x1296P)/2MP(1920x1080P)/1.3MP(1280x960P)/1MP(1280x720P) |
| Second stream | 704x576(D1), 704x288(2CIF), 352x288(CIF), 640x360 |
| Record & Live frame rate | 25fps at 4MP/3MP/2MP/1.3MP/1MP, 15fps at second stream |
| Bitrate control | 32Kbps ~ 6Mbps, VBR, CBR, I-Frame interval |
| Video Analysis | |
| Intelligent video analysis | Tripwire, Perimeter |
| Intelligent alarm | Advanced motion detection, Recognize only persons from all the moving objects |
| Intelligent codec | 256kbps for 1080P video stream, 1GB storage for 24 hours recording |
| Intelligent image | Advanced algorithm, Identifies persons clearly |
| Camera Functions | |
| WDR | 120dB, Auto/Manual adjustable |
| Day/Night | Auto(Outside/Inside), Color, B/W |
| Digital Noise Reduction | 3DNR (Close/Ordinary/Expert) |
| Light Compensation | BLC Off/On, 1 area, Customize design, HLC Off/On adjustable |
| White Balance | Auto/Manual/Lock/Nature/Sunshine/Day Light/Warm light |
| Other functions | Smart defog control, EIS(Image Stabilizer), Flip control, Motion detection, Privacy masking |
| Image Control | Brightness, Contrast, Sharpness, Saturation |
| OSD Display | 16x16, 32x32, 48x48, 64x64, adaptable size, Letters Such as Week, Date, Time, Total 3 Regions |
| Alarm Alert | On-screen alerts/Link out/FTP upload, PTZ trigger/E-MAIL/Pre-Post record(through NVR) |
| Network, Storage, Interface | |
| Protocol | TCP/IP, HTTP, FTP, DHCP, DNS, DDNS, MULTICAST, IPV4, NTP, UDP, Telnet |
| Pre & Post recording | Pre : 5 to 15sec, Post : 10 to 60 sec |
| Network storage | FTP(pre & post upload) |
| LAN port | 1x Port RJ-45, 10M/100M ethernet |
| Software Support | |
| Onvif | Yes, Profile S |
| CMS software | iCRYS series, up to 256CH(IP+NVR+Matrix) |
| 3rd Party VMS/NVR /CMS | Onvif/SDK |
| Mobile | Cloud support Android /iOS through NVR |
| User login | 8 User / 4 level of rights, Simultaneous login ≤7 user client |
| Snap shot management | Schedule, Link with FTP or Email |
| Encryption | Off/AES |

Technical Specifications

| Model No. | AM-DM4064-FMA2 |
|----------------------------|---|
| General | |
| Power supply | DC 12V ±15% & PoE (802.3af) |
| Power consumption | <3W @ IR Off, <7W @ IR ON |
| Voltage protection | TVS 6000V, Lightning/Surge 2000V(power) 1000V(RJ45) |
| IP & Vandal protection | IP67 |
| Reset switch | Yes |
| Operating temp. & humidity | -35°C ~ 65°C & 0% ~ 95% RH |
| Enclosure | Built-in 3 axis bracket, Metal+Plastic housing |
| Weight (g) & Dimension | <0.4Kg camera, 160.8mm(L) X 68mm(W) X 74.5mm(H) |

Dimension :

